

EXHIBIT B

96-031CON2

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application of

**Allan Scherr**

for

**[Network Accelerator]**

**NETWORK WITH CONFIGURABLE CACHING AT DATA NODES**

Cross Reference to Related Applications

This application is a continuation of copending U.S. Patent Application Serial No. 09/705,114 filed November 2, 2000 (now abandoned) which is a continuation of U.S. Patent Application Serial No. [09/659,482 filed April 20, 1998] 08/659,482 filed June 6, 1996 (now abandoned), which applications are assigned to the same assignee as this [invention] application.

Background Of The Invention10 Field of the Invention

The invention relates generally to the field of networking and in particular to the field of using auxiliary storage systems such as disk drives as caches for performance improvements in networks.

15 [Background]

As more users and more websites are added to the World Wide Web on the Internet, the content of the information transmitted on it also increases in complexity and quantity: Motion video, more complex graphics, audio transmissions, and 20 so on, place rapidly increasing performance demands on the Internet at all points. The problem faced by service and content providers as well as users is how to maintain or improve performance for a growing user base without constantly

creating the need for additional capacity or "bandwidth" in the network.

Websites and web browser software, such as provided by Netscape Communications Corporation (having a principal place of business in[, ] Mountain View, California) on the World Wide Web (WWW) [, ] use storage systems such as magnetic disks to store data being sent and received, and most of these also use a simple form of disk caching at the website or at the user site to improve performance and minimize re--transmissions of the same data. These typically use a "least recently used" (LRU) algorithm to maintain the most recently referred to data in the disk cache and a protocol that permits a user to request that a page be refreshed even if it is in the cache. However, as the traffic continues to grow, this method needs to be improved upon to provide the performance that may be required.

Traffic increases as subsequent requests are made for web pages that had been sent earlier, but are no longer in the local user's system. The same re-transmission will occur at other points in the network, thus degrading overall response time and requiring additional network bandwidth. One approach that is frequently used to tackle the problem is the use of faster transmission media to increase bandwidth. This takes large capital and labor expense to install and may also require replacement of modems and other equipment at various nodes.

Service providers that install faster transmission equipment must still match the speeds at which their users can send and receive data, thus bottlenecks can still occur that slow down performance and response times at the user's site.

5           Users who upgrade to faster transmission media may often have to scrap modems and other units that were limited to slower speeds. Somewhat less frequently, large-scale internal network wiring changes may need to be made, as well, often causing disruptions to service when problems are found during  
10 and after installation. With any of these changes, software changes may also be required at the user's site, to support the new hardware.

15           Despite the users' best efforts, a well-known phenomenon in network systems design, called the "turnpike" effect, may continually occur as users upgrade to faster transmission media. As United States interstate highway builders first  
20 observed in the 1950's, when better, "faster" highways were made available, more people tended to use them than were initially anticipated. A highway might have been designed to handle a specific amount of traffic, based on then present patterns and data. But once people learned how much faster and smoother travel on the new highway was, traffic might increase to two or three times the original projections, making the

highway nearly obsolete almost at the outset of its planned life.

Similar problems occur with users of the Internet and service and content providers. Many of the service providers and online system services have had difficulty adding systems and transmission links to keep up with such increases in traffic. As technology improves in all areas, content providers are providing more graphics, videos and interactive features that impose major new loads on the existing transmission systems. As companies and institutions install or expand local and wide area networks for their internal use, they are also linking them to Internet providers and sites, usually through gateways with "firewalls" to prevent unauthorized access to their internal networks. As these companies link their internal networks to the Internet and other external networks, usage and traffic on the Internet increases multi-fold. Many of these same companies and institutions are also content providers, offering websites of their own to others.

The content providers add to the problem of increased traffic in yet another way, when time-sensitive data is stored and transmitted. Stock quotes, for example, during the hours when a given exchange is open, are highly time sensitive. Web pages containing them or other market information need to be updated frequently during trading hours. Users who are tracking

such quotes, often want to insure that they have the latest update of the web page. If standard Least Recently Used (LRU) caching algorithms are used at the user site and this web page is in constant use, the cached copies may not be refreshed for several cycles of stock price changes: Here, caching data works to the user's disadvantage.

However, once that exchange closes, there should be no updates until the following business day. For the high-volume, high-visibility exchanges, this means traffic can reach peaks of congestion during trading hours. The network capacity used to keep up with this may lie dormant during off-peak hours. Most existing service and content providers on the Internet do not, at present, have an effective way to differentiate between these service levels in their prices or service offerings.

Private dial-up services, such as [Westlaw™ from] WESTLAW® of West Licensing Corporation [Group, having a principal place of business in Eagan, Minnesota,] or [Lexis/Nexis™] LEXIS/NEXIS® of the Reed Elsevier [PLC group having a principal place of business in Dayton, Ohio] or [CompuServe™ or America Online™] COMPUSERVE® of CompuServe, Incorporated or AMERICA ONLINE® of America Online, Incorporated, [having a principal place of business in Dulles, Virginia] have been able to offer differentiated pricing for networked access to certain kinds of data in their proprietary databases, but doing this is greatly

simplified when the choices are limited and relatively few in number. In most cases this is done on the basis of connect time and perhaps some additional fee per database accessed.

5 Data management methods, such as least recently used caching, can be applied to proprietary databases as well. Usually only one form of data or cache management is associated with a database, and the choice of a particular method of data and cache management has historically been based on the type of file being created.

10 On the Internet, by contrast, data requests can come from anywhere in the world for almost any topic in the world, to any content provider in the world. Patterns of access and timeliness requirements vary greatly from user to user. An educational institution that provides Internet services to its  
15 students and faculty will have one set of needs for access, and response times, while a business corporation user may have a completely different set of needs.

20 Access to data on the Internet also differs from dial-up access to proprietary databases in another way. The private dial-up service provider may not change the services offered for months or even years at a time. Data files may be updated, but the kinds of information that can be obtained may remain constant.



On the Internet, the opposite is true. Information that was not available three months ago anywhere in the world may now be available from several different sources. This is also true for the format of the information. In less than a three year time span, web pages have gone from text only, to text plus drawings, then to text plus high-resolution photographic-like images in several different formats. Sound is also available now from many sites. Web browsers now permit use of videos and interactive forms. Traditional network and data management techniques are hardpressed to keep up with these changes.

#### Summary of the Invention

It is an object of the present invention to provide a method and apparatus for improving network response time at one or more sites or nodes while reducing the amount of bandwidth used to carry a given load.

Another object of the present invention is providing improvements in network response time without requiring any changes in transmission media and transmission equipment.

Still another object of the present invention is providing a flexible method and apparatus for providing response time improvements that can readily be adjusted to different usage patterns.

A further object of the present invention is providing a method and apparatus that permits a service or content provider to offer differentiated levels of service and prices based on the type of data being transmitted.

5        [Summary of the Invention]

These and other objects are achieved by a [network] network accelerator storage caching system that may be inserted at any point in a network, to provide a configurable, scalable variety of cache management systems to improve response time.

10        Depending on the configuration(s) selected, the system may manage data or subsets of data in a storage cache on the basis of time- currency, page usage frequency, charging

considerations, pre-fetching algorithms, data-usage patterns, store-through methods for updated pages, least recently used

15        method, B-tree algorithms, or indexing techniques including named element ordering, among others. A preferred embodiment may embed the configurable cache management in the storage media, either as firmware in a storage controller or as

software executing in a central processing unit (CPU) in a

20        storage controller. In a preferred embodiment the system may be scaled in size and offer security for protected data.

It is an aspect of the present invention to provide improvements in response times.

It is another aspect of the present invention to reduce the bandwidth required in the vicinity of the invention to transmit information responsively.

Another aspect of the present invention is to enable  
5 configuring at each site to use the cache method(s) preferred by that site.

A further aspect of the present invention is allowing a site to trade storage space for transmission capacity or bandwidth.

10 Brief Description of the Drawings

Figure 1a is a schematic drawing of various sites on a network using the present invention.

Figure 1b [is a schematic drawing of illustrative] depicts alternative embodiments of a cache management system shown in  
15 Figure 1a. [the present invention.]

Figure 2a is a flow diagram that depicts the operation of configurator of the present invention.

Figure 2b is a more detailed flow diagram of the operation of the configurator of the present invention.

20 Figure 3 is a flow diagram of a least recently used cache management method used in the present invention.

Figure 4 is a flow diagram of a time-sensitive method of cache management used in the present invention.

Figure 5 is a flow diagram of a data usage cache management method used in the present invention.

Figure 6 is a flow diagram of a pre-fetch cache management method used in the present invention.

5 Figure 7 is a flow diagram of a charging cache management method used in the present invention.

Figure 8 is a flow diagram of a B-tree cache management method used in the present invention.

10 Figure 9 is a flow diagram of an indexed cache management method used in the present invention.

Figure 10a is a flow diagram of a store-through method of cache management used in the present invention. Figure 10b is a flow diagram of a data protection method according to the present invention.

15 Figure 11 is a block diagram of scripted variables and pseudo-code for a pre-fetch method of cache management used in the present invention.

20 Figure 12 is a block diagram of scripted variables and pseudo-code for a time sensitive method of cache management used in the present invention.

Figure 13 is a table showing the elements of a Uniform Resource Locator (URL).

Figure 14 is table showing some of the named elements that can be included in hyper-text markup language (HTML) pages.

Figure 15 is a schematic drawing of a form used in the present invention.

#### Detailed Description of the Invention

[In] Figure 1a[,] depicts a number of network sites or data nodes using the present invention [is shown]. In a preferred embodiment, cache management system 10[,] includes a control device 12[,] and storage units 14. Control device 12, in this preferred embodiment, includes firmware that executes the logic of the present invention. [Cache] A cache management system 10 is shown [here] in Figure 1a as being installed at various sites on an Internet network. For purposes of illustration, a service provider site 00, as one data node, is shown connected by transmission media [T1] T1 to a backbone link site 04. One or more backbone link sites 04, as another data node or other data nodes, may be used for sending and receiving messages through the network. Local site 06 is shown here as a data node connected to the network formed by one or more backbone links 04 via transmission media T2. Local site 06 might be a corporate firewall & gateway site connected to multiple user stations 08 as other data nodes inside an internal corporate network with a local area network as transmission media T3 or it could be a local service provider providing dial-up services to user stations 08 over

transmission media T3. Also shown in this Figure [1a,] 1a is a content provider site 02 as yet another data node.

*Sub C3* [In a preferred embodiment, as] As shown in Figure 1b, a storage unit 14 [of cache management system 10b is] may comprise a single storage unit 14 in a cache management system 10a. Cache management system 10b depicts a large magnetic recording disk array, such as a redundant array of independent disks in a single (RAID) system or multiple RAID systems installed at the site. A preferred embodiment might use even larger disk arrays such as one or more of EMC Corporation's (of Hopkinton, Mass.) Symmetrix™ disk array storage devices having as much as 1.1 gigabytes of storage for large backbone link sites 04 as shown in cache management system 10c.

As will be apparent to those skilled in the art, other types of fast random access storage media can be used as storage units 14, such as magneto-optical disks, or massive random access memory arrays. In whatever form, such storage devices act as cache memory device that are coupled to the data network.

In a preferred embodiment, cache management system 10 can be scaled up or down in storage capacity to meet site requirements. Similarly, in a preferred embodiment of the present invention[;-], control device 12 is the controller for the disk system, where such controller is also capable of

executing software or firmware implementations of the logic of cache management system 10. However, as will also be apparent to those skilled in the art, the logic of cache management system 10 could also be executed by a web browser at the CPU contained in the send and receive user station 08 connected to the network, as illustrated by user stations 08 in Figure 1b.

Returning to Figure 1a, cache management system 10 can be used at any or all of the types of sites listed above. For example, if service provider site 00 is used to manage the websites for a number of content providers, service provider site 00 may have its cache management system 10 configured to use either a page cache management method or a data usage frequency cache management method. This could also be related to a charging system that the service provider uses for billing its content providers. Alternatively, cache management system 10 could be configured for a store-through cache management method if the content providers used most frequently rely heavily on the use of interactive forms.

Still in Figure 1a, the administrator of backbone link 04 might prefer to configure its cache management system 10 to use page usage or data usage patterns for providing the best overall response times. As will be apparent to those skilled in the art, all of these administrative decisions and actions could also be done by an expert system dynamically. Similarly,

different sites might be configured differently. And also, within one site one set of configurations might apply to one subset of data and a different set to another subset of data.

Local site 06, however, might prefer to use a  
5 time-currency method of cache management. Transmissions over the Internet using the transmission control protocol/internet protocol [(TP/IP)] (TCP/IP) protocol have date stamps indicating the time at which they were sent, as do many other types of network protocols. If the information being  
10 transmitted is stock quote data, it is subject to frequent changes during the hours a given stock exchange is open, but after the close of a trading day, the closing prices will be valid until the next day of trading on that exchange. If such web-pages are cached using a "least recently used" method,  
15 important stock price changes may not be brought to a user's attention until that particular web-page is flushed or replaced in the cache and requires refreshing from the source. A time-currency method of cache management can be configured to refresh certain pages with one frequency, say every 15 minutes,  
20 during trading hours for a given exchange, and with another frequency, say until start of trading the next trading day, once the exchange has closed.

A local site 06 as shown in Figure 1a, might also prefer to use a data usage pattern or even a pre-fetch method of cache



management. This is particularly so where local site 06 is a corporate firewall/gateway site for an internal network. For example, if most of the internal users are likely to request pages from the same website, when they first log on, cache management system 10 at local site 06 could be configured to pre-fetch web pages from the requested site each time an internal user logs on and those pages are not already in cache storage. Or, data usage patterns could be tracked and used to manage cache management system 10 on that basis. To illustrate this, if users of a financial journal web page habitually go to a stock quote site when they finish the financial journal pages, this pattern can be combined with pre-fetching of the stock quote pages every time the financial journal pages are fetched. This, in turn, might be coupled with security provisions if access to such pages are to be limited to authorized users only.

When local site 06 is a firewall/gateway site to an internal corporate network, having a number of user sites 08 for its employees, these forms of usage based cache management may be more effective. There may be a greater commonality of interests, and hence data usage among the employees of a corporation, than there would be amongst a disparate grouping of unrelated users.

When local site 06 is a local service provider of dial-up Internet connections for a number of disparate user sites 08, different types of data usage patterns might be used to manage the cache and charge for services.

5           Still in Figure 1a, content provider site 02 might have still another subset of cache management methods that would work best for it.

10           Turning now to Figure 2a, an overall flow diagram of the present invention is shown. As shown at step 22, an initial entry is made to [the] a configurator of the present invention that acts as a cache memory manager. At step 24, the configurator establishes the parameters and other indicators which may be needed by the cache management method(s) selected by the site. As will be apparent to those skilled in the art, a  
15           number of methods can be used to indicate which of several options has been selected. In one preferred embodiment, a user supplying the appropriate password might interact with cache management system 10 at each startup or reboot of the site or of a web browser at the site. The options selected by the user  
20           may then be indicated by settings or switches in cache management system 10. For simpler cache management algorithms, this may be all that is required.

          However, for more complex algorithms, scripts can be prepared for the configurator, supplying additional details of

user criteria. Examples of these latter algorithms, with illustrative pseudo-code are shown in Figures 11 and 12.

In an alternative preferred embodiment, the methods to use for cache management can be specified when cache management system 10 is installed at a site.

5  
Sub C4  
In yet another embodiment, the methods to be used for cache management at one site could be specified by messages transmitted to it from another site or as a result of messages transmitted to it by a program or script running at the same site, such as a usage pattern analyzer.

10  
For example, such a usage pattern analyzer might track the statistics related to the likelihood that a type of page will already be in the cache when requested. If two methods of cache management are used at the site, pre-fetch for some subsets of data and least recently used (LRU) for others, a pattern  
15  
analyzer might calculate from history data that the probability of pre-fetch data types being in the cache is .5 versus a lower probability for LRU data. In this instance, preferential treatment would be given to the pre-fetch data when deciding which type should be replaced with new data.

20  
Sub C5  
Referring now to Figure 2b, the overall logic of the configurator of the present invention is shown. Here, step 24 from Figure 2a is expanded to show the logic of the configurator. It is essentially a series of decision blocks,

for analyzing the data supplied by the operator or by a script  
or a parameter list or a configuration message. Where a  
processing block is shown in Figure 2b, those skilled in the  
art will recognize that different types of setup and  
initialization are being performed in each process block.  
Switches may be set, addresses or indexes initialized and so  
on. The configurator, at decision block 24a checks to see if  
forms will be handled in a storethrough manner (as described  
below.) If yes, processing needed to effectuate that is  
performed at step 24b and the configurator proceeds next to  
decision block 24c to see if data security is to be provided.  
If yes, processing for that is done at step 24d. As will be  
apparent to those skilled in the art, various types of  
protection schemes could be implemented for data that will be  
stored in the cache, from a simple scheme, such as password  
protection, to more elaborate protections such as encryption.

Returning to the flow in Figure 2b, the system checks, at  
decision block 24e, to see whether any kind of indexing cache  
management method is selected. If it is, processing for the  
indexing method is done at step 24f. Next, the system  
determines whether a B-tree structure cache management method  
will be used, at decision block 24g. If so, processing for that  
is done at step 24h. Proceeding with Figure 2b, at decision  
block 24i the configurator checks to see if a usage caching

management is selected. If so, step 24j processes the usage  
caching option. Still going through Figure 2b, at decision  
block 24k, the configurator checks to see whether any pre-fetch  
cache management method option has been selected. The  
5 processing at step 24l might include the initial use of a  
web-crawler or robot to fetch initial pages. (See description  
below for further discussion.)

At decision block 24m in Figure 2b, the configurator  
checks to see whether any time sensitive method of cache  
10 management has been selected. If it has, the [system]  
configurator may analyze scripted data or parameter data to  
initialize the values to be used. (See below for use of scripts  
to supply such data.)

And lastly, in Figure 2b, the configurator checks at step  
15 24o to see if a least recently used cache management method is  
selected. If it has, then processing associated with it is done  
at step 24p. If no method has been selected, the configurator  
can institute a default method, such as LRU. Finally, the  
configurator logic returns to step 26 in Figure 2a, to proceed  
20 with the next tasks.

Now in Figure 2a, once the cache methods selected for the  
site have been configured, the present invention follows the  
general flow depicted. At decision block 26, the configurator  
asks whether data has been requested. If not, the present

invention enters a wait state at step 32, until a request comes in. As will be apparent to those skilled in the art, an alternative embodiment could create a task or subtask that is activated only when data requests are made and is suspended at other times.

5  
Sub  
C6 7

10 Again in Figure 2a, if data has been requested, the configurator checks at decision block 30, to see if the data is already in the cache. Depending on the cache management system used, this step may require either more or less time than existing systems. If B-tree or indexed caching methods have been selected, this step may be faster than existing systems. If time-sensitive methods have been selected, this step may take longer than existing systems.

15 If the data requested, usually a web page from a website, is already in the cache, in this example, storage units 14, the configurator proceeds to step 27[,] to supply that data from storage units 14 in answer to the request[,] and then to step 28, to update any indicators associated with the configured cache management method. Ultimately, it will  
20 proceed to step 32, and wait for the next request.

If, in Figure 2a, at decision block 30 it is determined that the data is not already in the cache (here, in storage units 14), a request will be made to fetch the data from the network at step 34.

At step 36, depending on the cache management method configured, the indicators, if any, for it will be updated. As will be described later, if an indexing method is used for cache management, the index address for storing this data might be computed at this point, if needed, to reflect a new piece of data. Then, at step 38, the data is stored in the cache, storage [units] unit(s) 14. It should be noted here, that if the data is not found because of a failure in storage unit 14, this does not present a critical reliability problem, since the data can simply be requested from the network until the failing storage unit 14 is replaced or repaired.

Turning now to Figure 3, a simple flow diagram of a least recently used (LRU) method of cache management is shown. When a new request comes in and the cache is full, as indicated at step 36a, in Figure 3, the system finds the least recently used (LRU) data at step 36b and replaces it with the new data at step 38. Then the system returns to step 32 in Figure 2a, to wait for the next request.

Figure 4, by contrast, outlines part of the processing for a time sensitive cache management method. There, once it is determined at decision block 30 that the data requested is already in the cache storage unit 14, it is retrieved from storage unit 14 at step 30a. Then it is checked at step 30b to see if the time-stamp on the found data is within the

time-stamp parameters configured for this method of cache management. If it is, then the system provides that data in answer to the request at step 27c and returns to step 28 in Figure 2a. If the data is not within the time-stamp parameters,  
5 a new, fresh copy is requested from the network by going to step 34 in Figure 2a.

An example of time sensitive parameters that can be verified in this way is shown in Figure 12. There scripted parameters CC are specified to indicate that pages are to be  
10 kept fresh during the trading hours of a stock exchange. In this example, the opening hours are said to be 1000 hours and the closing hour 1600 hours. During that time, the pages should be refreshed every 15 minutes, according to the scripted amount for value 1. Pseudo-code DD shows how this might be checked at  
15 decision block 30b of Figure 4.

A simple variation of the time-sensitive method might include a request that nothing cached be out of date more than some specified period of time. Very little network traffic is generated by simply requesting the version number or creation  
20 data of a web page, instead of the entire page or site.

In Figure 5, a flow diagram of a usage-based cache management system 10 is shown. On the Internet, data is found by means of Uniform Resource Locators (URL) addresses. A significant amount of information about usage is thus contained



merely in the address of a site. As shown in Figure 13, for example, for domain names, there are several standardized suffixes: com, edu, gov, mil, net, and org. These stand for: commercial, educational, government, military, network service  
5 provider, and nonprofit organization, respectively.

To illustrate usage based management, a company that markets products to educational institutions might want to give preferential treatment to all educational sites requested by the company's employees. Web pages retrieved from sites having  
10 the suffix .edu in their domain names, might be stored with preferential treatment in storage unit 14, so that these pages will not be replaced when the cache is full unless the cache is completely filled with .edu pages. Thus, even though other sites might be more or less frequently used, over time, a cache  
15 management system configured in this way will tend to give better response times for requests for .edu pages. As shown in Figure 5, at step 36a, the system configured to use this method of cache management will look for stored data that meets the "not an .edu page" usage requirement to determine where to  
20 store a newly retrieved page.

As will be apparent to those skilled in the art, the above use of standard Internet suffixes is illustrative only. Any of a number of other indicators, such as Uniform Resource Locators (URLs) or the identity of the requestor, for a few examples,

could also be used in connection with a usage based cache management system 10.

Alternatively, it is also possible that a site might want to track usage first, to establish data patterns by domain name suffix. In Figure 5, this is illustrated at steps 28a[,] and 36b where usage information is updated. This could be as simple a process as tracking the number of uses of each type of suffix over some specified period. The information gathered from this could be used to change the priorities of caching and replacing data. Other types of usage patterns that might be tracked could relate to images or sound files being referenced by a web page. Figure 14 identifies some of the types of image and sound files that can be included in or referred to in a web page.

In a similar way, information about the request can also be used to pre-fetch data from certain pages or websites. For example, as shown in Figure 13, [.]information about a particular web-site may be as specific as a "spot" location. A site having a large number of pages may have them individually addressable using the spot address. If a usage study indicates that users of a particular website almost always go from page 1 to pages 14-16, then this information could be configured into the cache management system as shown in Figure 6. If a request meets some pre-fetch criteria, as determined at step 26a in Figure 6, then an indicator can be set at step [27b] 26b to

pre-fetch some specified pages if they are not already in storage unit 14. These indicators could be automatically checked whenever a request is made from the network for data not in the cache.

5           Pre-fetching might also be appropriate for large files such as image and sound files. As illustrated in Figure 14, a hypertext reference [s1] "s1" to a sound file might cause the sound file to be pre-fetched when the page containing hypertext reference [s1] "s1" is retrieved. If frequent accesses are made  
10 by all the users at one site to this web page and all of its hypertext links, then pre-fetching the files referenced in the hypertext links will improve response times for such large files as sound, image and video.

15           In much the same way, charging methods of cache management can be created according to the method and apparatus of the present invention. An Internet service provider may want to charge its customers differently for different types of access. For example, requests for certain classes of domain names could be charged for differently. Requests for ".com" or commercial  
20 domain names, might be charged a higher rate than requests for ".org" nonprofit sites. If charges are also based on the need to refresh the cache, the system could track when a request is made that will cause a request to be made to the network (a refresh request). This is illustrated in Figure 7, where a

determination is made at step 26a as to whether or not the new request meets the criteria for changing the charging method. Thus, if the previous three requests had been for ".com" sites, and this request is for a ".org" site, and that causes the  
5 system to issue a request to the network, the charge rate would be changed to that for ".org" and the timed amounts updated.

As will be apparent to those skilled in the art, this method of cache management could also be combined with the time-sensitive cache management methods illustrated in Figure  
10 4. Thus, accesses made during the hours a given stock exchange is open could be billed at a higher rate than those made after trading hours. In yet another example of a time-sensitive cache management method, users could be charged for the "freshness" of the web pages fetched. If the user wants to insure that all  
15 pages of a certain type are less than 7 hours old, a premium charge could be associated with those requests.

In Figure 8, a flow diagram is shown for using a B-tree cache management method. B-trees are known to be a fast way to organize data stored on a disk, so that the disk can be  
20 searched quickly. In a preferred embodiment of the present invention, if large quantities of storage units 14 are used as part of cache management system 10, the use of B-trees may be advantageous for performance purposes. When a new request will result in a store to storage unit 14, the present invention

calculates the proper address for the B-tree store at step 36a as shown in Figure 8. In B-trees, a search tree is created of degree  $n$ , such that the root node has degree greater than or equal to 2 and every nonterminal node other than the root has degree  $k$ , where  $n/2$  is greater than or equal to  $k$  and  $k$  is greater than or equal to  $n$ .

An indexed method of cache management is shown in Figure 9. A very simple index might use the domain names and internet addresses for allocating space and addresses within storage unit 14. As indicated in Figure 9, when a new piece of data comes in, this index can be used to compute, at step 37, the proper address for storing the data in storage unit 14, the cache. When the data is stored in the cache's storage unit 14 at step 38, it is stored at the computed location.

An alternative embodiment of this indexing method might organize the index by the names of frequently accessed image, sound and video files as a top level priority, with other domain names and addresses having a second level priority. In this approach, preference would be given to those files (image, sound or video) that are most likely to require longer transmission times. When data in the cache is to be replaced, these longer files are not replaced except by other long file types and only after the secondary file types have been replaced.

A number of existing indexing schemes already exist on the Internet for use by programs known as search engines, spiders, web crawlers or robots. When a content provider places a web page on the world wide web, it may also include some index terms in the headers for the website. These indexes are picked up by the search engines and web crawlers when a search request is made over the Internet. An alternative preferred embodiment could use one of these indexing methods to establish the index for the cache management according to the method and apparatus of the present invention. One or more of these web crawlers or robots could also be used in another alternative preferred embodiment to do some or all of the pre-fetching referred to above.

Still another form of indexing or pre-fetching that could be used in an alternative preferred embodiment of the present invention is the technique known as mirroring. If users at a local site are constantly accessing a large website located outside the country, the cache management methods of the present invention might create a local mirror of that site in storage units 14, and use the protocols provided by the source for updating the mirror image. These normally include an initial transfer of all data using a file transfer protocol (FTP) - like protocol, and then regularly scheduled updates that cause any changes made at the source site to be

transferred to the mirror. Where the local site has a large amount of storage available for storage units 14, the present invention could include several mirrors in the cache as well as other indexes. Additionally, service providers could offer supplying the mirror files as one of their services. In this approach, updates would be sent to a local site by the service provider as they occur and without being solicited by a file transfer request from the local cache management system 10.

In Figures [1a] 10a and 10b, a store-through method of cache management is shown for use with interactive forms such as form f1 shown in Figures 14 and 15. Using any of a number of existing HTML interpreters or parsers (programs that analyze the HTML text present on a page to determine its contents), the configurator checks a [d] data request for the presence of forms at step 26, as shown in Figure 10a. If the data is a form, no check is made to see if it is already in the cache, since it is presumed that forms must be filled out freshly each time. Thus, at step 26a, the check is made to [;] see if the data contains a form. If it does, the [invention goes] method proceeds to step 34 (of Figure 2a) [to] and a request is made that a new copy be transmitted. If the request does not contain a form, the [configurator] method proceeds to decision block 30 (in Figure 2a) to see if the data is already in the cache.

In the example shown in Figure 15, where the form is a userid and password verification form, each user at a local site would fill in a different userid and password, hence storing one user's filled out form in the cache would be counterproductive for the other users. Other information that does not contain forms will be stored through, that is, placed in the cache according to any other method(s) configured.

In another preferred embodiment, security "doorways" are provided in cache management system 10, as shown in Figure 10b. Since such security is likely to include the use of some interactive form, the processing shown in Figure 10a is further modified to perform the logic shown in Figure 10b. Here, once it is established that a form is being transmitted, at step 26a, [the configurator next checks] a check is made at step 26e to see if the form's contents "open" the doorway. [First,] More specifically, a check is made at step 26e to see if the doorway is closed. If it is, at step 26e-1 the entries from the form are checked to see if they are valid for opening the doorway. If they [do] are -- that is, the userid and password have been accepted as valid, in this example -- then that page and those below in the index hierarchy are so marked at step 26f to enable this userid to store and access data in the cache. Once the "doorway" has been opened, the [system] operation of the method proceeds to step 26g to exit to step 30



(in Figure 2a) to see if the protected data is already in the cache. On the other hand, if the form's contents do not open the doorway, that is the userid and password have not been accepted as valid in this example, then the method okay??

5 proceeds via the "NO" output from question block 26e-1 to step 26b, and from there to step 34 in Figure 2a where is then proceeds in accordance with the flow diagram of Figure 2a.

The above described security provisions will work with existing Internet protocols such as http. As will be apparent to those skilled in the art, if the protocols change, or a different protocol is used, the security provisions may need to change as well. In anticipation of such changes, a preferred embodiment would perform the security checking in the cache management system 10, rather than in the applications software used at the site, to minimize the need for other changes.

As will be apparent to those skilled in the art, this or similar forms of security and protection, including such steps as encryption/ decryption for certain pages stored in the cache, may be required by service and content providers who offer to sell goods and services over the internet.

In a preferred embodiment, the logic of the present invention may be embodied in program code written in the C language, either as a software program stored in storage units 14 and executing in control device 12 of cache management

system 10, [5] or as firmware executing as part of control device 12 of cache management system 10. As will be apparent to those skilled in the art, other programming languages, such as PERL, or Pascal-or C++, or assembler, to name only a few, could be used instead. As mentioned earlier, while it is preferred that the code execute as part of control device 12 of cache management system 10, it could also be developed to execute as part of a web browser or server manager located at a local site.

10 *Sub B/2* Simplified embodiments of the present invention could also be implemented as [Unix] UNIX® of Unix System Laboratories, Inc or Unix shell or [Apple Macintosh] Applescript® of Apple Computer, Inc. scripts that execute in a server operating as one of the links in the network.

15 *Sub B/3* As will also be apparent to those skilled in the art, the present invention could also be implemented in hardware circuits using application specific integrated [circuits (ASICS)] circuit (ASIC) or gate [arrays] array techniques.

20 While the examples given here are drawn primarily from the Internet network, it will be apparent to those skilled in the art that the apparatus and method of the present invention can be applied to other networks, and similar applications, as well.

Those skilled in the art will appreciate that the embodiments described above are illustrative only and that other systems in the spirit of the teachings herein fall within the scope of the invention.

5 [ What is claimed as new is:]

What is claimed as new and desired to be secured by Letters Patent of the United States is:

*Inv  
Bill* >

*Bill*

Sub  
1A  
2

1 (Amended). A data node at each of at least first and second sites in a data network [comprising] wherein each of said data nodes comprises:

- 5           A) a cache memory device [connected] coupled to the data network, and
- B) a cache memory manager connected to said cache memory device for controlling communications between said cache memory device and other sites in the data network wherein each said cache memory manager controls transfers in response to one of at least two different cache [memory] management methods and wherein the cache memory management methods used at the first and second sites [is] are different.

15           2 (Amended). A data node as recited in claim 1 wherein said cache memory manager includes method storage means for storing [a] the plurality of different cache [memory] management methods and method selection means for selecting one of said cache memory management methods for controlling said cache

20           memory device.

          3 (Amended) A data node as recited in claim 2 wherein said cache memory manager additionally [including] includes

monitoring means for monitoring operations at said node and  
said method selection means responds to said monitoring means.

5 4 (Amended). A data node as recited in claim 2 wherein said  
cache memory manager additionally including means for receiving  
commands from other nodes and said method selection means  
responds to the received commands.

10 5 (Amended). A data node as recited in claim [5] 4 wherein one  
of said cache management methods is a least recently used cache  
management method.

15 6 (Amended). A data node as recited in claim [5] 4 wherein one  
of said cache management methods is a data usage cache  
management method.

20 7 (Amended). A data node as recited in claim [5] 4 wherein one  
of said cache management methods is a store-through cache  
management method.

8 (Amended). A data node as recited in claim [5] 4 wherein one  
of said cache management methods is a pre-fetch cache  
management method.

9 (Amended). A data node as recited in claim [5] 4 wherein one of said cache management methods is an indexing cache management method.

5 10 (Amended). A data node as recited in claim [5] 4 wherein one of said cache management methods is a charging cache management method.

10 12 (Amended). A data node as recited in claim 1 wherein each [of said] data [nodes] node operates with a different predetermined cache memory management method.

15 13 (Amended). A data node as recited in claim [12] 1 wherein said cache memory manager operates [in response to] with a predetermined cache memory management method that is different from the cache memory management method used at [the other network site] another data node.

20 [14. A data node as recited in claim 12 wherein said cache memory manager includes method storage means for storing a plurality of cache memory management methods and method selection means for selecting one of said cache memory management methods for controlling said cache memory device.]

15 (Amended). A data node as recited in claim [14] 13 wherein  
said cache memory manager includes a method storage means  
[stores] for storing, for selection, least recently used, data  
usage, store-through, pre-fetch, indexing, Btree and charge  
5 cache memory management methods.

16. A data node as recited in claim 15 additionally including  
monitoring means for monitoring operations at said node and  
said method selection means responds to said monitoring means.

10 17. A data node as recited in claim 15 wherein additionally  
including means for receiving commands from other nodes and  
said method selection means responds to the received commands.

## Abstract

A network accelerator storage caching system [that] manages a number of cache management systems and may be inserted at any point in a network[, ] to provide a configurable, scalable variety of cache management systems to improve perceived response time. Depending on the [configurations] configuration(s) selected, [the] a system cache management system may manage data in a storage cache on the basis of time-currency, page usage frequency, charging considerations, pre-fetching algorithms, data-usage patterns, store-through methods for updated pages, a least recently used method, B-tree algorithms, or indexing techniques including named element ordering, among others. [A] In a preferred embodiment [may embed] the configurable cache management [it] is embedded in the storage media, either as firmware in a storage controller or as software executing[; ] in a [CPU] central processing unit in a storage controller. In a preferred embodiment the system is [designed to be scalable and] [provide] provides security measures for protecting data and is dynamically configurable.